

Tyro Sedna 2 and 4 fold, wireless remote control

Manual 433 MHz

Musca transmitter and Aquarius receiver

Number of functions: 2 or 4, emergency stop, ON/OFF.

Button functions

To activate the Musca transmitter: press and hold the "ON" button for half a second.

To deactivate the Musca transmitter: press and hold the "OFF" button for half a second.

The Emergency stop is always active, so in a panic situation there will be no loss of time!

Mounting

To optimize the range of the Musca transmitter, it is recommended to place the antenna of the Aquarius receiver as high as possible and free of any metal objects. After connecting and mounting it is recommended to test the device before connecting the main powersource.

Cable scheme is as follows:

Description	Wirenumber
▼	5
▲	4
◀	2
▶	3
EM-stop	6
ON-button	-
OFF-button	-
Powersupply 8-38Vdc	1
Programming wire	7
Ground	Green/yellow



Please note: All systems are already programmed by the manufacturer.

Programming a new or extra Musca transmitter into the Aquarius receiver

If you wish to program an extra our new Musca transmitter into the Aquarius receiver, please follow the steps shown below:


Step	Description
1.	Make sure the Aquarius receiver has been connected properly and that it is powered
2.	Connect wire nr. 7 with the power (V+) for a maximum of 5 sec. (If you connect wire nr. 7 longer than 10 sec., all Sedna transmitters will be deleted from the system.)
3.	The status LED on the aquarius receiver will light up
4.	Press a random function button on the Sedna transmitter (the Sedna transmitter must be turned on)
5.	The status LED on the aquarius receiver will turn off
6.	Press again a random function button on the Sedna transmitter
7.	The status LED of the Aquarius receiver will flash for about 3 seconds
8.	After flashing, the transmitter has been programmed into the Aquarius receiver
9.	If you wish to program an additional Sedna transmitter, follow these steps again for every additional transmitter
10.	After programming reconnect wire nr. 7 to ground
11.	After mounting, wires that are not used can be cut off and must be isolated
12.	To delete all programmed Sedna transmitters connect wire no. 7 for at least 10 seconds to powersource (V+). To reprogram your Sedna transmitters into the Aquarius receiver, follow the steps 1 to 10 again

All deliveries will be subject to our general sales conditions, available on demand or through our website. Our products are certified for many applications. When mounting, always take into account the applicable machine directives.



Tyro Remotes
Bedrijvenpark Twente 1B
7602 KA Almelo
The Netherlands

Tel: +31-(0)546-588790
Fax: +31-(0)546-579490
E-mail: info@tyroremotes.eu
Website: www.tyroremotes.eu



Tyro Sedna 2 and 4 fold, wireless remote control

Technical specifications:

Aquarius receiver:

Operating voltage	8-38 Vdc
Fuse	10 A
Powersurge	17 mA
Max. output Amps	4A (at 24 Vdc) each output
Cable length	2.5 meters
IP classification	IP-68 (waterproof)

Sedna transmitter:

Range	Up to 100 meters
Frequency	433.92 MHz
Antenna	Integrated
Power surge standby	4 μ A.
Power surge while transmitting	12 mA (maximal)
Battery replace indicator	<u>If LED flashes slowly during transmitting, change battery</u>
Battery type	1 piece, 9V 600 mAh
Battery life whilst continuously transmitting	50 hours
Normal battery life	2 years
Impact proof	Max. 2 metres
IP classification	IP-65 (Splashing water proof)

Battery replacement in Sedna transmitter:

Carefully open the enclosure to prevent damage to the flat cable. To disconnect the flat cable lift the upper part of the connector, the flat cable will be released. Replace battery. After finishing you have to reconnect the flat cable and push down the upper part of the connector. Make sure there are no kinks in the flat cable, when screwing enclosures back on.

Standard options:

Sedna Transmitter and Musca receiver.

9V battery.

Receiver antenna 433MHz.

Emergency stop.

Power ON/OFF button.

2 or 4 function buttons.

Proprietor.

Standard 7 Sedna transmitters to program on one Aquarius receiver.



Extra options:

Coax extension cable and torque piece, available lengths: 1 meter, 2 meters or 5 meters.

The receiver can be programmed with a maximum of 48 transmitters.

Buttonlock function (bi-stable output contact).

Dimensions:

Sedna transmitter 150x71x31.

Aquarius receiver 95x150x30.

Weight:

Sedna transmitter: 190 gram.

Aquarius receiver: 508 gram.



Tyro Remotes
Bedrijvenpark Twente 1B
7602 KA Almelo
The Netherlands

Tel: +31-(0)546-588790
Fax: +31-(0)546-579490
E-mail: info@tyroremotes.eu
Website: www.tyroremotes.eu

